



NASCAR STYLE FRONT SPRINGS

CUSTOM RATES & TRAVELS AVAILABLE / CALL FOR DETAILS

9.500"	PART #	WIRE DIA.	I.D.	LENGTH	RATE	TRAVEL*
	SNX-455-095-0330-1500	0.577"	4.550"	9.500"	330 lb/in	2.633"
	SNX-453-095-0350-1500	0.577"	4.530"	9.500"	350 lb/in	2.727"
	SNX-443-095-0375-1500	0.577"	4.430"	9.500"	375 lb/in	2.974"
	SNX-433-095-0400-1500	0.577"	4.330"	9.500"	400 lb/in	3.162"
	SNX-423-095-0425-1500	0.577"	4.230"	9.500"	425 lb/in	3.384"
	SNX-415-095-0450-1500	0.577"	4.150"	9.500"	450 lb/in	3.537"
	SNX-415-095-0475-1500	0.586"	4.150"	9.500"	475 lb/in	3.673"
	SNX-415-095-0500-1500	0.594"	4.150"	9.500"	500 lb/in	3.811"

*AVERAGE TRAVEL CALCULATED AFTER 1500lb PRELOAD

8.750"	PART #	WIRE DIA.	I.D.	LENGTH	RATE	TRAVEL*
	SNX-455-087-0330-1500	0.577"	4.550"	8.750"	330 lb/in	1.883"
	SNX-453-087-0350-1500	0.577"	4.530"	8.750"	350 lb/in	1.977"
	SNX-443-087-0375-1500	0.577"	4.430"	8.750"	375 lb/in	2.224"
	SNX-433-087-0400-1500	0.577"	4.330"	8.750"	400 lb/in	2.412"
	SNX-423-087-0425-1500	0.577"	4.230"	8.750"	425 lb/in	2.634"
	SNX-415-087-0450-1500	0.577"	4.150"	8.750"	450 lb/in	2.787"
	SNX-415-087-0475-1500	0.586"	4.150"	8.750"	475 lb/in	2.923"
	SNX-415-087-0500-1500	0.594"	4.150"	8.750"	500 lb/in	3.061"
	SNX-415-087-0525-1500	0.601"	4.150"	8.750"	525 lb/in	3.093"
	SNX-415-087-0550-1500	0.607"	4.150"	8.750"	550 lb/in	3.182"

*AVERAGE TRAVEL CALCULATED AFTER 1500lb PRELOAD

8.500"	PART #	WIRE DIA.	I.D.	LENGTH	RATE	TRAVEL*
	SNX-455-085-0330-1500	0.577"	4.550"	8.500"	330 lb/in	1.633"
	SNX-453-085-0350-1500	0.577"	4.530"	8.500"	350 lb/in	1.727"
	SNX-443-085-0375-1500	0.577"	4.430"	8.500"	375 lb/in	1.974"
	SNX-433-085-0400-1500	0.577"	4.330"	8.500"	400 lb/in	2.162"
	SNX-423-085-0425-1500	0.577"	4.230"	8.500"	425 lb/in	2.384"
	SNX-415-085-0450-1500	0.577"	4.150"	8.500"	450 lb/in	2.537"
	SNX-415-085-0475-1500	0.586"	4.150"	8.500"	475 lb/in	2.673"
	SNX-415-085-0500-1500	0.594"	4.150"	8.500"	500 lb/in	2.811"
	SNX-415-085-0525-1500	0.601"	4.150"	8.500"	525 lb/in	2.843"
	SNX-415-085-0550-1500	0.607"	4.150"	8.500"	550 lb/in	2.932"

*AVERAGE TRAVEL CALCULATED AFTER 1500lb PRELOAD

8.250"	PART #	WIRE DIA.	I.D.	LENGTH	RATE	TRAVEL*
	SNX-455-083-0330-1500	0.577"	4.550"	8.250"	330 lb/in	1.383"
	SNX-453-083-0350-1500	0.577"	4.530"	8.250"	350 lb/in	1.477"
	SNX-443-083-0375-1500	0.577"	4.430"	8.250"	375 lb/in	1.724"
	SNX-433-083-0400-1500	0.577"	4.330"	8.250"	400 lb/in	1.912"
	SNX-423-083-0425-1500	0.577"	4.230"	8.250"	425 lb/in	2.134"
	SNX-415-083-0450-1500	0.577"	4.150"	8.250"	450 lb/in	2.287"
	SNX-415-083-0475-1500	0.586"	4.150"	8.250"	475 lb/in	2.423"
	SNX-415-083-0500-1500	0.594"	4.150"	8.250"	500 lb/in	2.561"
	SNX-415-083-0525-1500	0.601"	4.150"	8.250"	525 lb/in	2.593"
	SNX-415-083-0550-1500	0.607"	4.150"	8.250"	550 lb/in	2.682"

*AVERAGE TRAVEL CALCULATED AFTER 1500lb PRELOAD

8.000"	PART #	WIRE DIA.	I.D.	LENGTH	RATE	TRAVEL*
	SNX-455-080-0330-1500	0.577"	4.550"	8.000"	330 lb/in	1.133"
	SNX-453-080-0350-1500	0.577"	4.530"	8.000"	350 lb/in	1.227"
	SNX-443-080-0375-1500	0.577"	4.430"	8.000"	375 lb/in	1.474"
	SNX-433-080-0400-1500	0.577"	4.330"	8.000"	400 lb/in	1.662"
	SNX-423-080-0425-1500	0.577"	4.230"	8.000"	425 lb/in	1.884"
	SNX-415-080-0450-1500	0.577"	4.150"	8.000"	450 lb/in	2.037"
	SNX-415-080-0475-1500	0.586"	4.150"	8.000"	475 lb/in	2.173"
	SNX-415-080-0500-1500	0.594"	4.150"	8.000"	500 lb/in	2.311"
	SNX-415-080-0525-1500	0.601"	4.150"	8.000"	525 lb/in	2.343"
	SNX-415-080-0550-1500	0.607"	4.150"	8.000"	550 lb/in	2.432"

*AVERAGE TRAVEL CALCULATED AFTER 1500lb PRELOAD

7.500"	PART #	WIRE DIA.	I.D.	LENGTH	RATE	TRAVEL*
	SNX-455-075-0330-1500	0.577"	4.550"	7.500"	330 lb/in	0.633"
	SNX-453-075-0350-1500	0.577"	4.530"	7.500"	350 lb/in	0.727"
	SNX-443-075-0375-1500	0.577"	4.430"	7.500"	375 lb/in	0.974"
	SNX-433-075-0400-1500	0.577"	4.330"	7.500"	400 lb/in	1.162"
	SNX-423-075-0425-1500	0.577"	4.230"	7.500"	425 lb/in	1.384"
	SNX-415-075-0450-1500	0.577"	4.150"	7.500"	450 lb/in	1.537"
	SNX-415-075-0475-1500	0.586"	4.150"	7.500"	475 lb/in	1.673"
	SNX-415-075-0500-1500	0.594"	4.150"	7.500"	500 lb/in	1.811"
	SNX-415-075-0525-1500	0.601"	4.150"	7.500"	525 lb/in	1.843"
	SNX-415-075-0550-1500	0.607"	4.150"	7.500"	550 lb/in	1.932"

*AVERAGE TRAVEL CALCULATED AFTER 1500lb PRELOAD



425 S 7th St. Renton, WA 98055
p 425.255.1453 f 425.228.0780
www.rentoncoilsspring.com



UPG10 NASCAR STYLE REAR SPRINGS

CUSTOM RATES & TRAVELS AVAILABLE / CALL FOR DETAILS

16.000"	PART #	I.D.	LENGTH	RATE	TRAVEL*
	SCX-420-160-0050	4.200"	16.000"	50 lb/in	13.400"
	SCX-420-160-0075	4.200"	16.000"	75 lb/in	13.100"
	SCX-420-160-0100	4.200"	16.000"	100 lb/in	12.900"
	SCX-420-160-0125	4.200"	16.000"	125 lb/in	12.650"
	SCX-420-160-0150	4.200"	16.000"	150 lb/in	12.400"
	SCX-408-160-0175	4.080"	16.000"	175 lb/in	12.100"
	SCX-408-160-0200	4.080"	16.000"	200 lb/in	12.000"
	SCX-405-160-0225	4.050"	16.000"	225 lb/in	11.500"
	SCX-393-160-0250	3.930"	16.000"	250 lb/in	11.500"

*TOTAL TRAVEL CALCULATED FROM FREE LENGTH TO COIL-BIND

14.000"	PART #	I.D.	LENGTH	RATE	TRAVEL*
	SCX-405-140-0100	4.050"	14.000"	100 lb/in	11.000"
	SCX-405-140-0125	4.050"	14.000"	125 lb/in	10.800"
	SCX-405-140-0150	4.050"	14.000"	150 lb/in	10.600"
	SCX-405-140-0175	4.050"	14.000"	175 lb/in	10.500"
	SCX-406-140-0200	4.060"	14.000"	200 lb/in	10.500"
	SCX-406-140-0225	4.060"	14.000"	225 lb/in	10.300"
	SCX-407-140-0250	4.070"	14.000"	250 lb/in	10.000"
	SCX-407-140-0275	4.070"	14.000"	275 lb/in	10.000"
	SCX-396-140-0300	3.960"	14.000"	300 lb/in	9.900"
	SCX-396-140-0325	3.960"	14.000"	325 lb/in	9.850"
	SCX-397-140-0350	3.970"	14.000"	350 lb/in	9.800"
	SCX-397-140-0375	3.970"	14.000"	375 lb/in	9.690"

*TOTAL TRAVEL CALCULATED FROM FREE LENGTH TO COIL-BIND

11.200"	PART #	I.D.	LENGTH	RATE	TRAVEL*
	SCX-396-112-0300	3.960"	11.200"	300 lb/in	8.070"
	SCX-396-112-0325	3.960"	11.200"	325 lb/in	8.010"
	SCX-396-112-0350	3.960"	11.200"	350 lb/in	7.940"
	SCX-396-112-0375	3.960"	11.200"	375 lb/in	7.860"
	SCX-395-112-0400	3.950"	11.200"	400 lb/in	7.760"

11.200" cont.	PART #	I.D.	LENGTH	RATE	TRAVEL*
	SCX-396-112-0425	3.950"	11.200"	425 lb/in	7.700"
	SCX-396-112-0450	3.950"	11.200"	450 lb/in	7.650"
	SCX-396-112-0500	3.950"	11.200"	500 lb/in	7.710"
	SCX-396-112-0550	3.860"	11.200"	550 lb/in	7.570"

*TOTAL TRAVEL CALCULATED FROM FREE LENGTH TO COIL-BIND

9.200"	PART #	I.D.	LENGTH	RATE	TRAVEL*
	SCX-391-092-0200	3.910"	9.200"	200 lb/in	7.160"
	SCX-384-092-0250	3.840"	9.200"	250 lb/in	6.870"
	SCX-385-092-0300	3.850"	9.200"	300 lb/in	6.660"
	SCX-385-092-0350	3.850"	9.200"	350 lb/in	6.540"
	SCX-376-092-0400	3.760"	9.200"	400 lb/in	6.300"
	SCX-374-092-0450	3.740"	9.200"	450 lb/in	6.230"
	SCX-372-092-0500	3.720"	9.200"	500 lb/in	6.110"
	SCX-372-092-0550	3.720"	9.200"	550 lb/in	6.000"
	SCX-372-092-0600	3.720"	9.200"	600 lb/in	5.930"

*TOTAL TRAVEL CALCULATED FROM FREE LENGTH TO COIL-BIND



425 S 7th St. Renton, WA 98057
 p 425.255.1453 f 425.228.0780
 www.rentoncoilspring.com



BUMP STOP SPRINGS

1.000"	PART #	WIRE DIA.	I.D.	LENGTH	RATE	O.D.	MAX LOAD
	SBX7-089-010-0500	0.168"	0.890"	1.000"	500 lb	1.226"	240 lbs
	SBX7-089-010-1000	0.202"	0.890"	1.000"	1000lb	1.294"	410 lbs
	SBX7-089-010-1500	0.225"	0.890"	1.000"	1500 lb	1.340"	540 lbs
	SBX7-089-010-2000	0.243"	0.890"	1.000"	2000 lb	1.376"	640 lbs
	SBX7-089-010-2500	0.257"	0.890"	1.000"	2500 lb	1.404"	730 lbs
	SBX7-089-010-3000	0.270"	0.890"	1.000"	3000 lb	1.430"	790 lbs
	SBX7-089-010-3500	0.280"	0.890"	1.000"	3500 lb	1.450"	910 lbs
	SBX7-089-010-4000	0.289"	0.890"	1.000"	4000 lb	1.468"	980 lbs
	SBX7-089-010-4500	0.298"	0.890"	1.000"	4500 lb	1.486"	1030 lbs
	SBX7-089-010-5000	0.308"	0.890"	1.000"	5000 lb	1.506"	1070 lbs
1.500"	PART #	WIRE DIA.	I.D.	LENGTH	RATE	O.D.	MAX LOAD
	SBX7-089-015-0500	0.187"	0.890"	1.500"	500 lb	1.264"	380 lbs
	SBX7-089-015-1000	0.221"	0.890"	1.500"	1000lb	1.332"	600 lbs
	SBX7-089-015-2000	0.272"	0.890"	1.500"	2000 lb	1.434"	990 lbs
	SBX7-089-015-3000	0.305"	0.890"	1.500"	3000 lb	1.500"	1270 lbs
	SBX7-089-015-4000	0.329"	0.890"	1.500"	4000 lb	1.548"	1620 lbs
	SBX7-089-015-5000	0.350"	0.890"	1.500"	5000 lb	1.590"	1800 lbs
	SBX7-089-015-6000	0.366"	0.890"	1.500"	6000 lb	1.622"	2050 lbs
	SBX7-089-015-7000	0.381"	0.890"	1.500"	7000 lb	1.652"	2270 lbs
	SBX7-089-015-8000	0.394"	0.890"	1.500"	8000 lb	1.678"	2440 lbs
	SBX7-089-015-9000	0.407"	0.890"	1.500"	9000 lb	1.704"	2680 lbs
2.000"	PART #	WIRE DIA.	I.D.	LENGTH	RATE	O.D.	MAX LOAD
	SBX7-089-020-0500	0.209"	0.890"	2.000"	500 lb	1.308"	490 lbs
	SBX7-089-020-1000	.0251"	0.890"	2.000"	1000lb	1.392"	810 lbs
	SBX7-089-020-1500	0.280"	0.890"	2.000"	1500 lb	1.450"	1070 lbs
	SBX7-089-020-2000	0.303"	0.890"	2.000"	2000 lb	1.496"	1270 lbs
	SBX7-089-020-3000	0.337"	0.890"	2.000"	3000 lb	1.564"	1650 lbs
	SBX7-089-020-4000	0.361"	0.890"	2.000"	4000 lb	1.614"	2010 lbs
	SBX7-089-020-5000	0.382"	0.890"	2.000"	5000 lb	1.654"	2270 lbs
	SBX7-089-020-6000	0.402"	0.890"	2.000"	6000 lb	1.694"	2510 lbs
	SBX7-089-020-7000	0.418"	0.890"	2.000"	7000 lb	1.726"	2730 lbs
	SBX7-089-020-8000	0.432"	0.890"	2.000"	8000 lb	1.754"	2960 lbs
	SBX7-089-020-9000	0.445"	0.890"	2.000"	9000 lb	1.780"	3140 lbs
	SBX7-089-020-10000	0.457"	0.890"	2.000"	10000 lb	1.804"	3300 lbs
	SBX7-089-020-11000	0.467"	0.890"	2.000"	11000 lb	1.824"	3550 lbs
	SBX7-089-020-12000	0.478"	0.890"	2.000"	12000 lb	1.846"	3640 lbs

2.500"	PART #	WIRE DIA.	I.D.	LENGTH	RATE	O.D.	MAX LOAD
	SBX7-089-025-0750	0.250"	0.890"	2.500"	750 lb	1.390"	800 lbs
	SBX7-089-025-1000	0.269"	0.890"	2.500"	1000lb	1.428"	1020 lbs
	SBX7-089-025-1500	0.300"	0.890"	2.500"	1500 lb	1.490"	1370 lbs
	SBX7-089-025-2000	0.325"	0.890"	2.500"	2000 lb	1.540"	1630 lbs
	SBX7-089-025-3000	0.363"	0.890"	2.500"	3000 lb	1.616"	2030 lbs
	SBX7-089-025-4000	0.390"	0.890"	2.500"	4000 lb	1.670"	2410 lbs
	SBX7-089-025-5000	0.414"	0.890"	2.500"	5000 lb	1.718"	2800 lbs
	SBX7-089-025-6000	0.435"	0.890"	2.500"	6000 lb	1.760"	3280 lbs
	SBX7-089-025-7000	0.452"	0.890"	2.500"	7000 lb	1.794"	3390 lbs
	SBX7-089-025-8000	0.468"	0.890"	2.500"	8000 lb	1.826"	3640 lbs
	SBX7-089-025-9000	0.482"	0.890"	2.500"	9000 lb	1.854"	3960 lbs
	SBX7-089-025-10000	0.495"	0.890"	2.500"	10000 lb	1.880"	4160 lbs
	SBX7-089-025-11000	0.507"	0.890"	2.500"	11000 lb	1.904"	4380 LBS
	SBX7-089-025-12000	0.519"	0.890"	2.500"	12000 lb	1.928"	4780 LBS

3.000"	PART #	WIRE DIA.	I.D.	LENGTH	RATE	O.D.	MAX LOAD
	SBX7-089-030-0500	0.237"	0.890"	3.000"	500 lb	1.364"	680 lbs
	SBX7-089-030-1000	0.286"	0.890"	3.000"	1000lb	1.462"	1140 lbs
	SBX7-089-030-1500	0.320"	0.890"	3.000"	1500 lb	1.530"	1480 lbs
	SBX7-089-030-2000	0.346"	0.890"	3.000"	2000 lb	1.5825"	1830 lbs
	SBX7-089-030-3000	0.386"	0.890"	3.000"	3000 lb	1.662"	2470 lbs
	SBX7-089-030-4000	0.416"	0.890"	3.000"	4000 lb	1.722"	2990 lbs
	SBX7-089-030-5000	0.442"	0.890"	3.000"	5000 lb	1.774"	3180 lbs
	SBX7-089-030-6000	0.463"	0.890"	3.000"	6000 lb	1.816"	3590 lbs
	SBX7-089-030-7000	0.482"	0.890"	3.000"	7000 lb	1.854"	3920 lbs
	SBX7-089-030-8000	0.499"	0.890"	3.000"	8000 lb	1.888"	4230 lbs
	SBX7-089-030-9000	0.514"	0.890"	3.000"	9000 lb	1.918"	4580 lbs
	SBX7-089-030-10000	0.529"	0.890"	3.000"	10000 lb	1.948"	4750 lbs
	SBX7-089-030-11000	0.541"	0.890"	3.000"	11000 lb	1.972"	5180 lbs
	SBX7-089-030-12000	0.554"	0.890"	3.000"	12000 lb	1.998"	5310 lbs

3.500"	PART #	WIRE DIA.	I.D.	LENGTH	RATE	O.D.	MAX LOAD
	SBX7-089-035-1000	0.301"	0.890"	3.500"	1000lb	1.492"	1280 lbs
	SBX7-089-035-1500	0.336"	0.890"	3.500"	1500 lb	1.562"	1680 lbs
	SBX7-089-035-2000	0.363"	0.890"	3.500"	2000 lb	1.616"	2040 lbs
	SBX7-089-035-3000	0.405"	0.890"	3.500"	3000 lb	1.700"	2610 lbs
	SBX7-089-035-4000	0.437"	0.890"	3.500"	4000 lb	1.764"	3130 lbs
	SBX7-089-035-5000	0.465"	0.890"	3.500"	5000 lb	1.820"	3625 lbs
	SBX7-089-035-6000	0.488"	0.890"	3.500"	6000 lb	1.866"	4025 lbs
	SBX7-089-035-7000	0.508"	0.890"	3.500"	7000 lb	1.906"	4425 lbs
	SBX7-089-035-8000	0.526"	0.890"	3.500"	8000 lb	1.942"	4800 lbs
	SBX7-089-035-9000	0.543"	0.890"	3.500"	9000 lb	1.976"	5210 lbs
	SBX7-089-035-10000	0.558"	0.890"	3.500"	10000 lb	2.006"	5400 lbs
	SBX7-089-035-11000	0.572"	0.890"	3.500"	11000 lb	2.034"	5710 lbs
	SBX7-089-035-12000	0.585"	0.890"	3.500"	12000 lb	2.060"	6010 lbs

4.000"	PART #	WIRE DIA.	I.D.	LENGTH	RATE	O.D.	MAX LOAD
	SBX7-089-040-1000	0.314"	0.890"	4.000"	1000lb	1.518"	1421 lbs
	SBX7-089-040-1500	0.351"	0.890"	4.000"	1500 lb	1.592"	1846 lbs
	SBX7-089-040-2000	0.379"	0.890"	4.000"	2000 lb	1.648"	2242 lbs
	SBX7-089-040-3000	0.423"	0.890"	4.000"	3000 lb	1.736"	2883 lbs
	SBX7-089-040-4000	0.456"	0.890"	4.000"	4000 lb	1.802"	3508 lbs
	SBX7-089-040-5000	0.484"	0.890"	4.000"	5000 lb	1.858"	4010 lbs
	SBX7-089-040-6000	0.508"	0.890"	4.000"	6000 lb	1.906"	4470 lbs
	SBX7-089-040-7000	0.529"	0.890"	4.000"	7000 lb	1.948"	4921 lbs
	SBX7-089-040-8000	0.550"	0.890"	4.000"	8000 lb	1.990"	5376 lbs
	SBX7-089-040-9000	0.568"	0.890"	4.000"	9000 lb	2.026"	5661 lbs
	SBX7-089-040-10000	0.584"	0.890"	4.000"	10000 lb	2.058"	6020 lbs
	SBX7-089-040-11000	0.599"	0.890"	4.000"	11000 lb	2.088"	6325 lbs
	SBX7-089-040-12000	0.613"	0.890"	4.000"	12000 lb	2.116"	6624 lbs



425 S 7th St. Renton, WA 98055
 p 425.255.1453 f 425.228.0780
www.rentoncoilspring.com



AUTOMOTIVE DETROIT-STYLE LOCKER SPRINGS

PART #	INSTALLED HEIGHT	LOAD @ INSTALLED HEIGHT
TS-263-294-063-058	0.625"	58 LB
TS-263-294-063-068	0.625"	68 LB
TS-263-294-063-078	0.625"	78 LB
TS-263-294-063-088	0.625"	88 LB

*CUSTOM LOADS AVAILABLE (CALL FOR DETAILS)



425 S 7th St. Renton, WA 98057
p 425.255.1453 f 425.228.0780
www.rentoncoilsspring.com



RCS
Renton Coil Spring
AUTOMOTIVE COIL-OVER SPRINGS

UPG10 (COIL-BIND)

CUSTOM RATES & TRAVELS AVAILABLE / CALL FOR DETAILS

14.000"	PART #	I.D.	LENGTH	RATE	TRAVEL*
	SCX-308-137-0100	3.000"	13.700"	100 lb/in	10.750"
	SCX-308-135-0125	3.000"	13.500"	125 lb/in	10.500"
	SCX-308-135-0150	3.000"	13.500"	150 lb/in	10.300"
	SCX-308-130-0175	3.000"	13.000"	175 lb/in	9.750"
	SCX-308-130-0200	3.000"	13.000"	200 lb/in	9.600"
	SCX-308-130-0225	3.000"	13.000"	225 lb/in	9.450"

*AVERAGE TRAVEL CALCULATED FROM FREE LENGTH TO COIL-BIND

X3 (NON COIL-BIND)

CUSTOM RATES & TRAVELS AVAILABLE / CALL FOR DETAILS

14.000"	PART #	I.D.	LENGTH	RATE	TRAVEL*
	SCX3-303-140-0125	3.000"	14.000"	125 lb/in	9.900"
	SCX3-303-140-0150	3.000"	14.000"	150 lb/in	9.780"
	SCX3-303-140-0175	3.000"	14.000"	175 lb/in	9.400"
	SCX3-303-140-0200	3.000"	14.000"	200 lb/in	9.150"
	SCX3-303-140-0225	3.000"	14.000"	225 lb/in	9.050"
	SCX3-303-140-0250	3.000"	14.000"	250 lb/in	_____"
	SCX3-303-140-0275	3.000"	14.000"	275 lb/in	_____"
	SCX3-303-140-0300	3.000"	14.000"	300 lb/in	_____"

*AVERAGE TRAVEL CALCULATED FROM FREE LENGTH TO MAX TRAVEL



425 S 7th St. Renton, WA 98057
 p 425.255.1453 f 425.228.0780
 www.rentoncoilsspring.com